

Ballon à ébullition à fond rond, trois cols inclinés

Réf. : –



SPÉCIFICATIONS PAR MODÈLE

N° de catalogue	Capacité (ml)	Douille	Douille latérale	Conditionnement
128/1	100	24/29	14/23	1
128/2	250	24/29	14/23	1
128/3	250	24/29	19/26	1
128/4	500	24/29	14/23	1
128/5	500	24/29	19/26	1
128/6	1000	24/29	14/23	1
128/7	1000	24/29	19/26	1
128/8	1000	34/35	24/29	1
128/9	2000	24/29	19/26	1
128/10	2000	34/35	19/26	1
128/11	2000	34/35	24/29	1
128/12	3000	34/35	19/26	1
128/13	3000	34/35	24/29	1
128/14	5000	34/35	19/26	1
128/15	5000	40/38	19/26	1
128/16	5000	50/42	19/26	1

N° de catalogue	Capacité (ml)	Douille	Douille latérale	Conditionnement
128/17	5000	55/44	19/26	1
128/18	5000	34/35	24/29	1
128/19	5000	40/38	24/29	1
128/20	5000	50/42	24/29	1
128/21	5000	55/44	24/29	1
128/22	10000	34/35	19/26	1
128/23	10000	40/38	19/26	1
128/24	10000	50/42	19/26	1
128/25	10000	55/44	19/26	1
128/26	10000	34/35	24/29	1
128/27	10000	50/42	24/29	1
128/28	10000	55/44	24/29	1
128/29	20000	34/35	19/26	1
128/30	20000	50/42	19/26	1
128/31	20000	55/44	19/26	1
128/32	20000	34/35	19/26	1
128/33	20000	34/35	24/29	1
128/34	20000	50/42	24/29	1
128/35	20000	55/44	24/29	1
128/39	25	19/26	14/23	1
128/40	50	19/26	14/23	1
128/41	100	24/29	19/26	1

CARACTÉRISTIQUES TECHNIQUES